

THE KAIVAC® 1250

EQUIPMENT SPECIFICATIONS

■ DESCRIPTION

Water Tank	45.2 l
Spray Time	16 Minutes
Restroom Fixtures/Tank	~32
Flow Rate	2.8 l/min
Pressure	34.5 bars
Vac Tank	30.27 l
See-Through Vac Tank	Yes
Dump Hose	55.9 cm Long
Toilet Dumping	Yes
Vac Tank Cleanout	100% @ 27 secs
Method of Dumping	Drain Hose
Vac Motor Lift	330 cm
Vac CFM	3.72 l/min
HEPA Blow Feature	48 km/h
HEPA Filtered Exhaust	Yes - Replaceable

■ CHEMICAL

Molded-In Chemical Holder	AAA (1), FA (2)
Chemical Switching	Single/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

■ ELECTRICAL

Volts	115V / 230V
Volts (Univers	115V / 230V
Amps Total	14.5 amp
GFCI	Yes

■ CORDS AND HOSES

Vac Hose	15.24 m Slinky
Spray Line	13.71 m
Quick-Connect Gun	Yes
Electric Cord	7.62 m
Blow Hose	10 m Slinky

■ BODY

Rotational Mold	Yes
Removable Engine Compartment	Yes - Black Box Technology
Weight	42.41 kg
Size (H x L x W)	96.5 x 55.9 x 50.8 cm
Hard Rubber Tire	12.7 cm
Casters	10.2 cm, locking
Stair Climbing Wheels	Yes
Handle	Molded-In
Parking Brake	Yes

■ TOOLS INCLUDED

Vac Wand Aluminum	2-Piece
Hi & Lo Squeegee Head	Yes
Blow Nozzle	Yes
Training Materials	Video and Placard
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
60 l Tote Bag	Yes

■ WARRANTY WITH KAIVAC CHEMICAL USAGE*

Body	5 Years
Parts	3 Years
Labor	1 Year

See your local representative for warranty information.



kaivac cleaning systems™

Complete Cleaning For Healthy Results™