

# THE KAIIVAC® 2150

## EQUIPMENT SPECIFICATIONS

### DESCRIPTION

Water Tank	79.5 l
Restroom Fixtures/Tank	~55
Spray Time	21 Minutes
Flow Rate	3.7785 l/min
Pressure	34.5 bars
Vac Tank	72 l
See-Through Vac Tank	Yes
Dump Hose	106.7 cm Long
Toilet Dumping	Yes
Vac Tank Cleanout	100%
Method of Dumping	Drain Hose
Vac Motor Lift	330 cm
Vac CFM	3,172 l/min
HEPA Blow Feature	480 km/h
HEPA Filtered Exhaust	Yes - Replaceable

### CHEMICAL

Molded-In Chemical Holder	5 l (2), 1 l (2)
Chemical Switching	Dual/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

### ELECTRICAL

Volts	220-240 V; 50-60 Hz
Amps Total	14.5 amp
GFCI	Yes

### CORDS AND HOSES

Vac Hose	22.9 m
Spray Line	22.9 m
Quick-Connect Gun	Yes
Electric Cord	15 m
Blow Hose	10 m

### BODY

Rotational Mold	Yes
Weight	72.1 kg
Size (H x L x W)	129.5 x 81.3 x 61.0 cm
Flat-free Non-marking Pneumatic Tires	25.4 cm (2)
Casters	12.7 cm, locking (2)
Stair Climbing Wheels	Yes
Handle	Molded-In
Tray	Molded-In
Parking Brake	Yes

### TOOLS INCLUDED

Vac Wand Aluminum	2-Piece
36 cm Squeegee Head	Yes
Blow Nozzle	Yes
Training Materials	Video and Placard
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
60 l Tote Bag	Yes

### WARRANTY

See your local representative for warranty information.



**kaivac cleaning systems™**

Complete Cleaning For Healthy Results™